

product information

CNC EDM MACHINES

Moving Table



S60 CNC



S60 CNC EMC

ANOTRONIC LTD.™

Unit 3, Hollingdon Depot, Stewkley Road, Soulbury,
Nr. Leighton Buzzard, Beds., LU7 0DF. England.
Telephone +44 (01525) 270261 Fax +44 (01525) 270235
E-Mail sales@anotronic.com
Internet <http://www.anotronic.com>



AN85-1

POWER SUPPLY SPECIFICATIONS

Model	Max. Normal Output current LV/HV (AMP)	Max.machining Speed(mm ³ /MIN)	Min. Electrode Wear ratio (Under)	Best surface Finish (Ra μm)	Power Consumption (KVA)
30A	30/5	200	0.2%	0.2	4
45A	45/5	300	0.2%	0.2	5.5
60A	60/5	400	0.2%	0.2	7
90A	90/5	600	0.2%	0.2	10
120A	120/5	800	0.2%	0.2	13

MACHINE SPECIFICATIONS

Model	S50 CNC	S60 CNC	S90 CNC
Table size	600x360	660x380	820x500
Worktank(L)	760	950	1100
(W)	490	580	700
(H)	270	300	300
X axis travel	300	400	500
Y axis travel	200	300	400
Z Axis	Servo	300	300
	Backslide		
Table-Quill Distance (Max)	490	500	710
Maximum Electrode Weight	90Kg	120Kg	220Kg
Maximum Table Load	600Kg	800Kg	1200Kg
Dielectric tank capacity(L)	200	400	600
Filters	2	2	3
Machine Weight	1650Kg	1900Kg	2500+ 210Kg
Power Supply	30A/5A 45A/5A 60A/5A	30A/5A 45A/5A 60A/5A	60A/5A 90A/5A 120A/5A

ANOTRONIC LTD.™

Unit 3, Hollingdon Depot, Stewkley Road, Soulbury,
 Nr. Leighton Buzzard, Beds., LU7 0DF. England.
 Telephone +44 (01525) 270261 Fax +44 (01525) 270235
 E-Mail sales@anotronic.com
 Internet <http://www.anotronic.com>

